



1.

AlphaGloss Roof Coating is recommended for the refurbishment of your tile or metal roof surface and is designed to withstand the tough Australian climate and enhance the appearance of your renovation project.

AlphaGloss roof coatings utilise tough acrylic resin combined with fade resistant pigments to produce an environmentally friendly, low VOC coating that is durable, flexible, and resistant to ultra-violet sunlight.

AlphaGloss Roof Coating is available in a gloss finish and in a wide range of colours, including Colorbond® equivalents.

AlphaGloss Roof Coating is recommended and used as a decorative coating that can be brushed, rolled or sprayed to the following properly prepared and sealed weathered surfaces:

- Concrete and Unglazed Terracotta Roof Tiles
- Metal Roof Surfaces including Colorbond®
- Fibro Cement Sheeting.

TYPICAL PROPERTIES

Gloss Level	Gloss	VOC	< 30g/L
Colour	Wide range of colours	Solids %	31.2 +/- 5%
Number of Coats	2 minimum	Viscosity (Spindle 6 @ 10rpm)	32,000 cps +/- 2%
Touch Dry	30 minutes	pH	8.5 +/- 2%
Recoat	2 hours	Toxicity	Lead Free
Full Cure	14 days	Shelf Life	24 months
<i>All figures are quoted at 25°C and 50% relative humidity</i>		Wet Film (per coat)	250 µm
Application	Brush, Roll or Spray	Dry Film (per coat)	70 µm
Tip Size	521 - 523	Size	20L
Coverage	4 m ² /L	Note: Conduct a small test patch in an inconspicuous area to ensure suitability and product performance for your application.	
Clean Up	Water		
Thinner	Not Recommended		

HEALTH & SAFETY

- **Contact Poisons Information Centre (Phone Australia: 13 11 26) or a doctor.**
- **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.
- **IF ON SKIN:** Wash with plenty of soap and water.
- **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF EXPOSED OR CONCERNED:** Get medical advice/attention.
- Wear appropriate protective clothing, gloves, eye/ face protection and suitable respirator.
- Use this product in a well-ventilated area.

RECOMMENDATIONS & PRECAUTIONS

- Ensure that application is in accordance with Alphaglaze recommendations.
- Due care and consideration should be taken where water collection methods are present. Alphaglaze recommends allowing 10 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.
- The surface preparation is the responsibility of the Builder, Renovator, Contractor or Applicator. It is also the responsibility of the Applicator to ensure that the substrate is of an acceptable standard prior to the application of the Alphaglaze Coating System.

TRAFFICABILITY: After full cure, AlphaGloss is suitable for light traffic during periodic service maintenance. Due care must be taken to avoid any damage (e.g. tools, equipment or any sharp objects).

DISCLAIMER: The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use on the Alphaglaze product are beyond Alphaglaze's control. Alphaglaze recommends that the applicator of this product conducts a small test patch in an inconspicuous area to determine the suitability of the Alphaglaze material and its recommendations prior to use or application.