



## ALPHASEAL- STANDARD

## TECHNICAL DATA SHEET

Alphaseal - Standard is a water based 100% acrylic sealer primer supplied as a milky white substance. When dried the solution appearance becomes a clear film. Having a high resin content allows Alphaseal – Standard to be used on a variety of substrates including concrete roof surfaces, terracotta roof tiles, along with metal, zincalume and Colorbond® roof surfaces.

## FEATURES & BENEFITS

- **Water Based** – Easy application and easy clean up.
- **Good Adhesion** - Excellent adhesion to a variety of substrates.
- **Fast Dry** – Recoat/overcoat after 2 hours.

## TYPICAL PROPERTIES

<b>Colour</b>	Clear
<b>Number of Coats</b>	1 minimum
<b>Touch Dry</b>	30 minutes
<b>Overcoat</b>	2 hours
<b>Full Cure</b>	14 days
<i>All figures are quoted at 25°C and 50% relative humidity</i>	
<b>Coverage</b>	8 - 10 m <sup>2</sup> /L
<b>Clean Up</b>	Water
<b>Thinner</b>	Not Recommended

<b>Application</b>	Brush, Roll or Airless Spray
<b>Tip Size</b>	517
<b>Components</b>	1
<b>Toxicity</b>	Lead free. Dry film is non-toxic.
<b>Dry Film (per coat)</b>	39 µm
<b>Size</b>	5L and 15L buckets
<b>Shelf Life</b>	24 months

**Note:** Conduct a small test patch in an inconspicuous area to ensure suitability and adhesion of product for your application.

## HEALTH & SAFETY

## RECOMMENDATIONS & PRECAUTIONS

- **Contact Poisons Information Centre (Phone Australia: 13 11 26) or a doctor.**
- **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.
- Use this product in a well-ventilated area.
- Ensure that the application of the product is in accordance with Alphaglaze recommendations.

- **IF ON SKIN:** Wash with plenty of soap and water.
- **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF EXPOSED OR CONCERNED:** Get medical advice/attention.
- Wear appropriate protective clothing, gloves, eye/ face protection and suitable respirator.
- Due care and consideration should be taken where water collection methods are present. Alphaglaze recommends allowing 10 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.
- The surface preparation is the responsibility of the Builder, Renovator, Contractor or Applicator. It is also the responsibility of the Applicator to ensure that the substrate is of an acceptable standard prior to the application of the Alphaglaze Coating System.

**DISCLAIMER:** The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use on the Alphaglaze product are beyond Alphaglaze's control. Alphaglaze recommends that the applicator of this product conducts a small test patch in an inconspicuous area to determine the suitability of the Alphaglaze material and its recommendations prior to use or application.